

Optimized storage, extended taste





GRAM



AT A GLANCE

The Compact benefits

Solid foundation

With a reputation for delivering smart refrigeration solutions, Hoshizaki engineers cabinets for better storage solutions for Chefs and kitchen operators.





COMPACT AND VERSATILE

With our solid engineering and design background, Hoshizaki develops cabinets for better storage solutions for Chefs and kitchen operators.



UNIFORM TEMPERATURES

Automatic defrost and a smart air distribution system ensures correct and uniform temperatures at all times preserving the taste, texture and nutritional content of your fresh goods.



SPACE SAVING MODULARITY

The COMPACT undercounter models are designed to fit under worktops in commercial workplaces. They can be positioned as free-standing cabinet. The full-height storage cabinets boast a small footprint, perfect for limited space in back of house environment.



EASY CLEANING

Rounded corners and base, seamless surfaces and removable door gasket ensures cleaning routines become a quick and simple task.



WASTE REDUCTION

The practical anti-tilting shelves prevent spillage.



FULL HEIGHT INTEGRATED HANDLE

Easy grip and easy access for cleaning.



HIGH STANDARD IN HYGIENE

The one piece inner lining with its smooth surfaces and seamless construction allows for a straight forward cleaning routine.

Small footprint. High performance.

A quick guide to the Compact series.



© MPACI SERIES





The GRAM COMPACT series offers a rare combination: they are professional food safe cabinets with a compact size and with excellent energy ratings for its class.

These small space storage cabinets are easy to fit in, especially when space is of a premium, making the COMPACT series a popular choice amongst small kitchen operators who do not require heavy duty gastronorm refrigeration.

Ideal for commercial kitchens. (Front of House/ Back of House)

Suitable for operations in ambient temperatures of up to +30°C.

Climate Class 4: normal-duty cabinets (KG-glass door refrigerators-are also climate class 4) Climate Class 3: glass door freezers.



4

<11

0

Built-in LED light (available in glassdoor cabinets only).

<12

Wide magnetic removable door gasket with triple insulation area provides an effective seal, reduces escaping cold air.

<13

Efficient air distribution inside the cabinet allows chilled air flow with a specially designed air channel.

<14

Reversible door (solid or glass doors).

<15

According to your preference: Legs or Castors available (420 models only).

< 16

Clear display. Membrane switchboard for easy cleaning.

< 17

Automatic re-evaporation of condensate water.

<18

Door Lock.

1Low noise levels.

2> Air circulation system ensure temperature stability.

3> Removable door gasket for easy cleaning.

4>

Full-height integrated handle. Easy grip and easy access for cleaning.

5> Anti-spillage shelves with tilt prevention.

> 6> Automatic defrost.

7

Compact 220 fits under work tops or can be stacked if required.

8>

Variety of cabinet size and temperature ranges.

9> Seamless structure for easy cleaning inside the cabinet.

10 >

Optional: pedal door opener, which can be placed on left or right side.











A range of Compact cabinets for versatile kitchen set-ups

ABOUT COMPACT

The COMPACT series offers a rare combination: they are professional food safe cabinets with a compact size and with excellent energy ratings for its class. The COMPACT series benefits from a small footprint and versatility. Compact food storage has never been better.









THE COMPACT FAMILY









220









	COMPACT K220R DR G E	COMPACT K220L DR G E	COMPACT KG220R DR G E	COMPACT KG220L DR G E
Item number	151220010	161220010	154220010	164220010
Temperature range	+1/+12°C	+1/+12°C	+1/+12°C	+1/+12°C
Volume, gross (I)	123	123	123	123
Net usable volume (I)	77	77	77	77
Outside dimensions $W \times D \times H$ (mm)	595 x 645 x 833	595 x 645 x 833	595 x 667 x 833	595 x 667 x 833
Weight (kg)	43	43	49	49
Weight, packed (kg)	52	52	58	58
Insulation (mm)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)
Refrigeration capacity at -10°C (W)	63	63	82	82
Refrigeration capacity at -25°C (W)	-	-	-	-
Connection	230V/50 Hz	230V/50 Hz	230V/50 Hz	230V/50 Hz
Connection load (Watt)	70	70	100	100
Energy efficiency class	A++	A++	А	A
Energy consumption AEC (Annual)	197	197	429	429
Climate class	4	4	4	4
Sound level db(A)	38.8	38.8	38.8	38.8
Refrigerant	R600a	R600a	R600a	R600a
GWP (Global Warming Potential)	3	3	3	3
Number of shelves	2	2	2	2
Shelf size of top shelves (mm)	483.8 x 433	483.8 x 433	483.8 x 433	483.8 x 433
Shelf size of bottom shelves (mm)	484.7 x 300	484.7 x 300	484.7 x 300	484.7 x 300
Maximum number of shelves	9	9	9	9
	€ 1.680	€ 1.510	€ 1.980	€ 1.820

ITEM	ADD ON	AVAILABLE FOR	Notes for accessories
1519898	Wire shelf white 485*433	All models	COMPACT K420R L1 DR G E
1519899	Wire shelf white bottom 485*300	All models	
761230421	White perforated shelf (486x433mm)	All models	L1 indicates that these models are fitted with legs (1129663)

Please find accesories list recommendation for models with legs.

220










	COMPACT F220R DR G E	COMPACT F220L DR G E	COMPACT FG220R DR G E	COMPACT FG220L DR G E
Item number	153220010	163220010	155220010	165220010
Temperature range	-25/-5°C	-25/-5°C	-19/-5°C	-19/-5°C
Volume, gross (I)	123	123	123	123
Net usable volume (I)	77	77	77	77
Outside dimensions $W \times D \times H$ (mm)	595 x 645 x 833	595 x 645 x 833	595 x 667 x 833	595 x 667 x 833
Weight (kg)	44	44	52	52
Weight, packed (kg)	53	53	61	61
Insulation (mm)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)
Refrigeration capacity at -10°C (W)	-	-	-	-
Refrigeration capacity at -25°C (W)	186	186	186	186
Connection	230V/50 Hz	230V/50 Hz	230V/50 Hz	230V/50 Hz
Connection load (Watt)	150	150	150	150
Energy efficiency class	A	A	С	С
Energy consumption AEC (Annual)	700	700	906	906
Climate class	4	4	3	3
Sound level db(A)	39.2	39.2	39.2	39.2
Refrigerant	R600a	R600a	R600a	R600a
GWP (Global Warming Potential)	3	3	3	3
Number of shelves	2	2	2	2
Shelf size of top shelves (mm)	483.8 x 433	483.8 x 433	483.8 x 433	483.8 x 433
Shelf size of bottom shelves (mm)	484.7 x 300	484.7 x 300	484.7 x 300	484.7 x 300
Maximum number of shelves	9	9	9	9
	€ 1.730	€ 1.560	€ 2.120	€ 1.980

ITEM	ADD ON	AVAILABLE FOR	Notes for accessories
1519898	Wire shelf white 485*433	All models	COMPACT K420R L1 DR G E
1519899	Wire shelf white bottom 485*300	All models	The second se
761230421	White perforated shelf (486x433mm)	All models	L1 indicates that these models are fitted with legs (1129663)


Please find accesories list recommendation for models with legs.




420









	COMPACT K420R L1 DR G E	COMPACT K420L L1 DR G E	COMPACT KG420R L1 DR G E	COMPACT KG420LL1 DR G E
ltem number	151421010	161421010	154421010	164421010
Temperature range	+1/+12°C	+1/+12°C	+1/+12°C	+1/+12°C
Volume, gross (I)	343	343	343	343
Net usable volume (I)	265	265	265	265
Outside dimensions W x D x H (mm)	595 x 645 x 1876-1911	595 x 645 x 1876-1911	595 x 667 x 1876-1911	595 x 667 x 1876-1911
Weight (kg)	76	76	89	89
Weight, packed (kg)	87	87	99	99
Insulation (mm)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)
Refrigeration capacity at -10°C (W)	122	122	122	122
Refrigeration capacity at -25°C (W)	-	-	-	-
Connection	230V/50 Hz	230V/50 Hz	230V/50 Hz	230V/50 Hz
Connection load (Watt)	120	120	130	130
Energy efficiency class	В	В	D	D
Energy consumption AEC (Annual)	310	310	670	670
Climate class	4	4	4	4
Sound level db(A)	39.8	39.8	39.8	39.8
Refrigerant	R600a	R600a	R600a	R600a
GWP (Global Warming Potential)	3	3	3	3
Number of shelves	5	5	5	5
Shelf size of top shelves (mm)	483.8 x 433	483.8 x 433	483.8 x 433	483.8 x 433
Shelf size of bottom shelves (mm)	484.7 x 300	484.7 x 300	484.7 x 300	484.7 x 300
Maximum number of shelves	26	26	26	26
	€ 2.230	€ 2.010	€ 2.710	€ 2.490

ITEM	ADD ON	AVAILABLE FOR	Note
1519898	Wire shelf white 485*433	All models	СОМРА
1519899	Wire shelf white bottom 485*300	All models	
1129664	Set of stainless steel (SS) adjustable foot 135-200mm	K420, F420, KG420, FG420	L1 indic are fitte
1129665	Set of castor for Compact	K420, F420, KG420, FG420	
761230421	White perforated shelf (486x433mm)	All models	Please f recomm
819581052	Foot pedal for door	All models	with leg

es for accessories

PACT K420R L1 DR G E

icates that these models ted with legs (1129663)

find accesories list mendation for models egs.

420









	COMPACT F420R L1 DR G E	COMPACT F420L L1 DR G E	COMPACT FG420R L1 DR G E	COMPACT FG420LL1 DR G E
Item number	153421010	163421010	155421010	165421010
Temperature range	-25/-5°C	-25/-5°C	-19/-5°C	-19/-5°C
Volume, gross (I)	343	343	343	343
Net usable volume (I)	265	265	265	265
Outside dimensions W x D x H (mm)	595 x 645 x 1876-1911	595 x 645 x 1876-1911	595 x 667 x 1876-1911	595 x 667 x 1876-1911
Weight (kg)	77	77	97	97
Weight, packed (kg)	88	88	110	110
Insulation (mm)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)
Refrigeration capacity at -10°C (W)	-	-	-	-
Refrigeration capacity at -25°C (W)	217	217	217	217
Connection	230V/50 Hz	230V/50 Hz	230V/50 Hz	230V/50 Hz
Connection load (Watt)	140	140	140	140
Energy efficiency class	С	С	В	В
Energy consumption AEC (Annual)	1086	1086	1152	1152
Climate class	4	4	3	3
Sound level db(A)	39.7	39.7	39.7	39.7
Refrigerant	R600a	R600a	R600a	xR600a
GWP (Global Warming Potential)	3	3	3	3
Number of shelves	5	5	5	5
Shelf size of top shelves (mm)	483.8 x 433	483.8 x 433	483.8 x 433	483.8 x 433
Shelf size of bottom shelves (mm)	484.7 x 300	484.7 x 300	484.7 x 300	484.7 x 300
Maximum number of shelves	26	26	26	26
	€ 2.370	€ 2.150	€ 2.940	€ 2.780

ITEM	ADD ON	AVAILABLE FOR
1519898	Wire shelf white 485*433	All models
1519899	Wire shelf white bottom 485*300	All models
1129664	Set of stainless steel (SS) adjustable foot 135-200mm	K420, F420, KG420, FG420
1129665	Set of castor for Compact	K420, F420, KG420, FG420
761230421	White perforated shelf (486x433mm)	All models
819581052	Foot pedal for door	All models

Notes for accessories

COMPACT K420R L1 DR G E

L1 indicates that these models are fitted with legs (1129663)

Please find accesories list recommendation for models with legs.



Hoshizaki Europe B.V. Headquarters Export EMENA, Burgemeester Stramanweg 101, 1101 AA Amsterdam, the Netherlands sales@hoshizaki.nl +31 (0)20 691 84 99 www.hoshizaki-europe.com